

4820i

Industrial Cordless 2D Imager



Overview

From the global leader in handheld imaging solutions, the 4820i Industrial Cordless 2D Imager is designed to provide unmatched data collection performance and versatility for applications that demand maximum reliability in the harshest working environments.

Powered by Adaptus™ Imaging Technology 5.0, the 4820i delivers high-performance, omni-directional linear and 2D bar code reading plus the versatility of digital image capture. With Adaptus 5.0, enterprises have the ability to capture and process more data than ever before with a single device.

Built for scan-intensive applications requiring a ruggedized solution, the 4820i features our highest drop specification and an IP54 rating to guarantee protection against the penetration of dust and liquid. However, unlike other industrial grade solutions, the 4820i features best-in-class ergonomics – ensuring maximum user comfort and productivity.

The 4820i features a unique design that not only allows tool-free access to the battery, but also eliminates the need to dock the scanner for charging – a true advantage for operations where downtime is not an option.

Bluetooth® cordless connectivity allows users to move freely and eliminates the hazard of cables in fast-paced environments – all the while ensuring fast, accurate data communication.

The 4820i Advantage

Premium Features

High Performance and Versatile Data Collection: Adaptus Imaging Technology 5.0 provides aggressive, omni-directional reading of all linear and 2D bar codes, plus enables digital image capture.

Tool-Free Battery Access: Thumbwheel end-cap allows easy access to the battery, permitting employees to quickly swap batteries and keep working instead of docking the scanner for charging – a key feature for operations running multiple shifts.

Simplified Device Configuration Through Advanced Software Assets: Visual Xpress™ software enables device programming and configuration on a host system through an easy-to-use Windows®-based graphical user interface.

Leading Combination of Ergonomics and Durability: Rugged housing is specified to withstand 50 drops from 6.5 feet (2m) and certified to IP54 standards, while still being ergonomic and easy-to-use.

Presentation Scanning Capability: Can be programmed to scan in presentation mode while docked in the base, enabling hands-free scanning.

Industry-Standard Features

Wireless Connectivity: Bluetooth v1.2 radio enables movement up to 33 feet (10m) from the base, and reduces interference with other wireless systems. Up to 7 imagers can communicate to 1 base, reducing the total cost of ownership.

User Feedback Designed for Extreme Environments: Adjustable, extra loud “good read” beeper and dual LED indicators ensure reliable & intuitive feedback even in noisy environments.

Long-Lasting Lithium-Ion Battery: Powers up to 50,000 scans per full charge ensuring maximum uptime.

4820i Specifications

Performance

Illumination LEDs: 626nm ±30nm
Aiming:
Green LED Aimer: 526nm ±30nm
Image: VGA, 752x480. Binary, TIFF, or JPEG output.
Working Range:

4820i SR	8.3 mil Linear (.021cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil PDF417 (.038cm)	35 mil MaxiCode (.089cm)
Near	3.0 in. (7.6cm)	1.6 in. (4.1cm)	4.0 in. (10.2cm)	2.6 in. (6.6cm)	1.8 in. (4.6cm)	1.5 in. (3.8cm)
Far	7.1 in. (18.0cm)	12.7 in. (32.3cm)	5.7 in. (14.5cm)	8.5 in. (21.6cm)	9.7 in. (24.6cm)	12.5 in. (31.8cm)
4820i SF	7.5 mil Linear (.019cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil Data Matrix (.038cm)	15 mil QR Code (.038cm)
Near	2.0 in. (5.1cm)	1.5 in. (3.8cm)	2.3 in. (5.8cm)	1.7 in. (4.3cm)	1.3 in. (3.3cm)	1.7 in. (4.3cm)
Far	6.0 in. (15.2cm)	8.4 in. (21.3cm)	5.5 in. (14.0cm)	7.1 in. (18.0cm)	7.0 in. (17.8cm)	6.7 in. (17.0cm)

Pitch/Skew Angle: ±40°
Motion Tolerance: 4 in. (10 cm) per second

Radio

Frequency: 2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Bluetooth v. 1.2
Range: 33 ft. (10 m) typical
Data Rates: 720 KBps

Battery

Battery: Lithium Ion
Capacity: 2,200 mAh
Number of Scans: 50,000
Expected Hours of Operation: 16 hours
Charge Time at 9 Vac: 4 hours for full charge from full discharge

Symbologies

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite
Linear: Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS, Codablock, and ISBT 128 Concatenation*
 *requires a paid license
Postal: Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands Post)
OCR Fonts: OCR-A, OCR-B
Interfaces: Keyboard wedge, USB, TTL level RS-232, wand emulation, TTL level Serial Wedge, and IBM 46XX retail terminals.

Mechanical/Electrical

	4820i Scanner	2020 Base
Dimensions		
Weight:	9.6 oz. (272 g)	8.8 oz. (250 g) w/o cable
Height:	6.2 in. (15.7 cm)	3.1 in. (7.9 cm)
Power Requirements		
Input Voltage:	4.2 V internal battery	4.5 to 12 VDC (host) 8.5 to 9.5 VDC brick
Current Draw		125mA max @ 5V (no charging) 100 mA max @ 12V (no charging) 825mA max @ 12V (charging)
Environmental		
Sealing:	IP 54	IP 41
Temperature		
Operating:	14° to 122°F (-10° to 50°C)	32° to 122°F (0° to 50°C)
Storage:	-40° to 158°F (-40° to 70°C)	-40° to 158°F (-40° to 70°C)
Humidity:	0 to 95%, non condensing	up to 95%, non condensing
Mechanical Shock:	Functional after 50 drops from 6.5 ft. (2.0 m)	Functional after 50 drops from 3.3 ft. (1 m)

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV, 2005 Sunrise Compliant

Worldwide Offices

Offices Serving North America
 Skaneateles Falls, NY
 Tel: +1 315 685 8945
 or, in North America: +1 800 582 4263
 napresales@handheld.com
 Charlotte, NC
 Tel: +1 704 998 3998
 or, in North America: +1 800 582 4263
 napresales@handheld.com

Offices Serving Europe, Middle East, and Africa

Europe
 Tel: +31 (0) 40 29 01 600
 eusales@handheld.com
United Kingdom
 Tel: +44 (0) 1 925 240055
 eusales@handheld.com
Italy
 Tel: +39 02 7254 6754
 Info.italy@handheld.com

France
 Tel: +33 (0) 1 41 158220
 Info.france@handheld.com
Germany
 Tel: +49 (0) 7 477 151377
 Info.germany@handheld.com
Spain
 Tel: +34 93 228 78 68
 Info.spain@handheld.com

Offices Serving Asia and the Pacific Rim

Hong Kong
 Tel: +852 2511 3050
 appresales@handheld.com
Japan
 Tel: +813 5770 6312
 appresales@handheld.com
Shanghai
 Tel: +86 21 6361 3818
 appresales@handheld.com
Malaysia
 Tel: +603-6201 9020
 appresales@handheld.com

Offices Serving Latin America

Naples, Florida
 Tel: +1 239 263 7600
 lapresales@handheld.com
Rio De Janeiro
 Tel: +55 21 2178 0500
 lapresales@handheld.com
Mexico
 Tel: +52 55 5203 2100
 lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") ©1999-2007. All rights reserved. Printed in the U.S.A.

Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.