



Specification Sheet

8000D Linerless

Features:

- Direct thermal, linerless, paper label with a permanent acrylic adhesive
- Excellent print quality
- Good scratch/smear resistance
- Not to be used in applications using chemicals
- Excellent print quality when used in linerless printer.
- No liner allows more labels per roll and no waste
- Available in white (05987RM)

Suggested Applications:

- Mobile point of sale labeling
- Work in process labeling
- Applications that do not allow the use of a liner

Material Construction:

Description		Caliper
Facestock	White smooth silicone topcoated paper	3.0 mil
Adhesive	Permanent, rubber-based	1.2 mil
Total		4.2 mil +/- 10%

Temperature Performance:

- Minimum Application Temperature: 40° F (4° C)
- Service Temperature: -40° F to 140° F (-40° C to 60° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use



Applications with Chemicals

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
DT			X	X	X												

X indicates acceptable chemical resistance

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

