



Specification Sheet

8000T Cling

Features:

- Thermal transfer, vinyl static cling label
- Recommended for labeling applications requiring clean removability
- Available in white (66741RM)
- May be used in desktop printers
- For best performance use 3200 ribbon

Suggested Applications:

- Oil Change labeling
- Temporary parking identification
- Window labeling
- Work in process labeling

Material Construction:

	Description	Caliper
Facestock	White topcoated cling vinyl film	6.0 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
Total		8.5 mil +/- 10%

Temperature Performance:

- Minimum Application Temperature: 32° F (0° C)
- Service Temperature: -40° F to 200° F (-40° C to 93° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Two years



Suggested Ribbons for Applications with Chemicals

Ribbon	Relevant Automotive Chemicals					
	Windex	Windshield Washer Fluid	Antifreeze	Motor Oil	Gasoline (Soak)	Gasoline (Rub)
3200 (for 8000T Cling White)	X	X	X	X	X	

X indicates acceptable performance

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

