



# Specification Sheet

## Z-Perform 1000T 7.5 mil Tag

### Features:

- Thermal transfer, smooth, uncoated 7.5 mil paper tag
- Good print quality with 2000 and 5319 wax ribbons
- Available in white (05168RM)

### Suggested Applications:

- General purpose ticketing
- Retail hang tags
- Inventory and shop floor tracking tickets
- Work in process tagging
- AIAG, LOGMARS and industrial inventory control tags

### Material Construction:

	Description	Caliper
Facestock	White smooth uncoated thermal transfer paper	7.5 mil
<b>Total</b>		7.5 mil +/- 10%

### Temperature Performance:

- Minimum Application Temperature: NA
- Service Temperature: -50° F to 200° F (-46° C to 93° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use



## Suggested Ribbons for Applications with Chemicals

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
<b>2000</b>																	
<b>5319</b>																	

NOTE: For guidance only, not to be used for setting specifications

### Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

